

OPTEC® EC-640

COLOR-PAVEMENT

Admixture for enhancing high-quality surfaces and to reduce efflorescence

Product Description

OPTEC EC-640 is used for the production of coloured concrete products from no-slump or semi-dry concrete.

The main fields of application include the production of paver blocks, kerbstones or slabs.

Properties/Mode of Action

Surface-active substances effect a better dispersion of the cement particles. The concrete becomes more homogenous and easier to compact, thereby increasing both, green strength and ultimate strength. Close textured surfaces are promoted by the formation of slurries on the surface during vibration.

The integral hydrophobic components make the capillary pores water-repellent. The combined action of a denser concrete matrix, water repellency of capillary pores and plasticizing, the transport of moisture is reduced in the capillaries. Thus, the dissolved calcium hydroxide can only migrate in small quantities to the surface resulting in a reduced tendency to effloresce.

Finished products are more uniform and more intense in colours.

Dosage and Use

OPTEC EC-640 is added with the gauging water, or to the readymix.

The concrete should be run as moist as possible in the block making machine in order to even increase the effect of OPTEC EC-640.

Special Information

Preliminary tests according to official national standards are always required before use!

Typical Properties

Typical Properties	
Effective component	Surfactants
Form	Liquid
Colour	Dark brown
Density	1.01 ± 0.01 g/cm ³
Freezing point	Approx. 0°C
pH-value	10.0 ± 1
Storage	Keep well closed in original containers. Keep well closed. Protect from excessive heat and frost.
Recommended dosage	3–4 ml/kg CEM Approx. 0.3–0.4 % of CEM
Delivery form	1010 kg containers; 200 kg drums; 23 kg cans
Physiological effect	May irritate skin and eyes; see MSDS.
Shelf-life	Approx. 12 month in closed original containers

gcpat.com | Customer Service: Tel: 01925 855330 Fax: 01925 855350

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

OPTEC is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2016 GCP Applied Technologies Inc. All rights reserved

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140 USA

GCP Applied Technologies (UK) Ltd., 830 Birchwood Boulevard, Birchwood, Warrington, WA3 7QZ United Kingdom GCP0082 OPTEC EC-640 GB UK 0817 al

