

	Project:
gcp applied technologies	Client:
GCP APPLIED TECHNOLOGIES 580/581 lpswich Road, Slough, Berkshire, SL1 4EQ, UK T: +44(0)1753 490000 E: uksales@gcpat.com W: www.gcpat.com	Title:

conjunction with all relevant product data sheets. Adprufe Design Criteria Concrete structures must be designed in accordance with BS EN 1992-1-1, BS EN 1992-1-2, BS EN 1992-3 and BS 8102, or a comparable code. Concrete containing Adprufe should be designed in accordance with the requirements of BS EN 1992-1-1 having a maximum crack width of 0.3mm water retaining structures should be designed in				
be brought to the attention of the designer of the structure, who is responsible for the waterproofing and structural design and for being aware of all the factors in the structural design that may impact on the waterproofing details, and approved by them ir writing. Final decisions and any recommendations must be approved by the designer BS8102:2009 6.2.4 The need for continuity in the waterproofing protection should also be considered when selecting a type of protection. In most circumstances, the protection should be continuous. For product installation this drawing is to be read in conjunction with all relevant product data sheets. Adprufe Design Criteria Concrete structures must be designed in accordance with BS EN 1992-11, BS EN 1992-1-2, BS EN 1992-3 and BS 8102, or a comparable code. Concrete containing Adprufe should be designed in accordance with the requirements of BS EN 1992-1-1 having a maximum crack width of 0.3mm water retaining structures should be designed in accordance with the SI 9192-3 having a maximum crack width of 0.2 mm, when the hydrostatic Pressure/wall thickness is 5 5.		Notes.		
6.2.4 The need for continuity in the waterproofing protection should also be considered when selecting a type of protection. In most circumstances, the protection should be continuous. For product installation this drawing is to be read in conjunction with all relevant product data sheets. Adprufe Design Criteria Concrete structures must be designed in accordance with BS EN 1992-1-1, BS EN 1992-1-2, BS EN 1992-1-3 and BS 8102, or a comparable code. Concrete containing Adprufe should be designed in accordance with the requirements of BS EN 1992-1-1 having a maximum crack width of 0.3mm water retaining structures should be designed in accordance with BS EN 1992-3 having a maximum crack width of 0.2 mm, when the hydrostatic Pressure/wall thickness is ≤ 5. endip Rev: Date: Description: Scale: NTS Project No:		be brought to the attenti structure, who is respon and structural design ar factors in the structural the waterproofing details writing. Final decisions a	ion of the designer of the sible for the waterproofing ad for being aware of all the design that may impact on s, and approved by them in and any recommendations	
a clip conjunction with all relevant product data sheets. Adprufe Design Criteria Concrete structures must be designed in accordance with BS EN 1992-1-1, BS EN 1992-1-2, BS EN 1992-3 and BS 8102, or a comparable code. Concrete containing Adprufe should be designed in accordance with the requirements of BS EN 1992-1-1 having a maximum crack width of 0.3mm water retaining structures should be designed in accordance with BS EN 1992-3 having a maximum crack width of 0.2 mm, when the hydrostatic Pressure/wall thickness is ≤ 5. emarks of id Technologies. Rev: Date: Description: Scale: NTS Project No:		BS8102:2009 6.2.4 The need for continuity in the waterproofing protection should also be considered when selecting a type of protection. In most circumstances, the protection should be		
Concrete structures must be designed in accordance with BS EN 1992-1-1, BS EN 1992-3 and BS 8102, or a comparable code. Concrete containing Adprufe should be designed in accordance with the requirements of BS EN 1992-1-1 having a maximum crack width of 0.3mm water retaining structures should be designed in accordance with BS EN 1992-3 having a maximum crack width of 0.2 mm, when the hydrostatic Pressure/wall thickness is ≤ 5. a clip emarks of ed Technologies. Rev: Date: Description: Scale: NTS Project No:		For product installation this drawing is to be read in		
emarks of ad Technologies. Rev: Date: Description: Scale: NTS Project No:		Adprufe Design Criteria Concrete structures must be designed in accordance with BS EN 1992-1-1, BS EN 1992-1-2, BS EN 1992-3 and BS 8102, or a comparable code. Concrete containing Adprufe should be designed in accordance with the requirements of BS EN 1992-1-1 having a maximum crack width of 0.3mm; water retaining structures should be designed in accordance with BS EN 1992-3 having a maximum crack width of 0.2 mm, when the hydrostatic		
emarks of ad Technologies. Rev: Date: Description: Scale: NTS Project No:	 a clip			
ed Technologies. Rev: Date: Description: Scale: NTS Project No:				
		Rev: Date: Desc	cription:	
		Scale: NTS	Project No:	
Drawn: Drawing No.:		Drawn:	Drawing No.:	
Checked: AD01-0516.dwg			_	