

writing. Final decisions and any recommendations must be approved by the designer

6.2.4 The need for continuity in the waterproofing protection should also be considered when selecting a type of protection.

In most circumstances, the protection should be continuous.

For product installation this drawing is to be read in conjunction with all relevant product data sheets.

## Adprufe Design Criteria

Concrete structures must be designed in accordance with BS EN 1992-1-1, BS EN 1992-1-2, BS EN 1992-3 and BS 8102, or a comparable code.

Concrete containing Adprufe should be designed in accordance with the requirements of BS EN 1992-1-1 having a maximum crack width of 0.3mm; water retaining structures should be designed in accordance with BS EN 1992-3 having a maximum crack width of 0.2 mm, when the hydrostatic Pressure/wall thickness is  $\leq 5$ .

## ADPRUFE / PREPRUFE PLUS INTERFACE DETAIL PLAN AT CONSTRUCTION JOINT

Project:

Adcor, Adprufe, Aerofil, BETEC, Bentorub, Bituthene, Hydroduct, Paraseal, Perm-A-Barrier, Preprufe Plus, Servidek, Servijoint, GCP Applied Technologies. Armourtape, Bitushield, Bitustik, Colflex, Pak Adhesive, PVC Edgetie, Servitape, Slipstrip and Preprufe ZipLap are trademarks of GCP Applied Technologies. This drawing is Copyright 2016 of GCP Applied Technologies. Permission for copying is granted only to employees, authorised representatives, customers, and specifiers to support the sale or use of GCP Applied Technologies products. All other rights are reserved.

Scale: NTS Project No:	Rev:	Date:	Description:	
	Scale:	NTS		Project No:

Drawing No.:

AD20-0516.dwg

Date:

gcp applied technologies GRACE CONSTRUCTION & PACKAGING

**GCP APPLIED TECHN** 

580/581 Ipswich Road, Slough, Be T: +44(0)1753 490000 E: uksales@gcpat.com W: www.gcpat.com

NOLOGIES	
erkshire, SL1 4EQ, UK	

Client: Drawn: Title: Checked: