

RC WALL / DECK INTERFACE PREPRUFE PLUS / SILCOR - CONFINED SITE SECTION

Adcor, Adprufe, Aerofil, BETEC, Bentorub, Bituthene, Hydroduct, Paraseal, Perm-A-Barrier, Preprufe Plus, Servidek, Servijoint, Servijoint, Servirufe, Servirufe, Serviseal, Servitite, Silcor, Solarshield and Vertiseal are registered trademarks of GCP Applied Technologies. Armourtape, Bitushield, Bitustik, Colflex, Pak Adhesive, PVC Edgetie, Servitape, Slipstrip and Preprufe ZipLap are trademarks of GCP Applied Technologies. This drawing is Copyright 2016 of GCP Applied Technologies. Permission for copying is granted only to employees, authorised representatives, customers, and specifiers to support the sale or use of GCP Applied Technologies products. All other rights are reserved.

gcp applied technologies	
GRACE CONSTRUCTION & PACKAGING	
GCP APPLIED TECHNOLOGIES	

Title:

580/581 lpswich Road, Slough, Berkshire, SL1 4EQ, UK
T: +44(0)1753 490000 E: uksales@gcpat.com W: www.gcpat.com

Project:

Client:

Scale: NTS

Date:

Drawn:

awn: Drawing No.:

Rev: Date: Description:

Checked:

SLCR16-0516

Project No:

comply with the recommendations of BS 6229: 2003 `Flat Roofs With Continuously Supported Coverings'.

must be approved by the designer.

This detail is for typical roof waterproofing

suit specific project conditions and design

applications only and may require modification to

requirements. The design and application is to

Roof Slabs / Podium Decks

Basements / Buried Decks

BS8102:2009

Notes.

General Waterproofing

All waterproofing details shown herein should

be brought to the attention of the designer of the

structure, who is responsible for the waterproofing

and structural design and for being aware of all the

factors in the structural design that may impact on the waterproofing details, and approved by them in writing. Final decisions and any recommendations

6.2.4 The need for continuity in the waterproofing protection should also be considered when selecting a type of protection.

In most circumstances, the protection should be continuous.

For product installation this drawing is to be read in conjunction with all relevant product data sheets and the Silcor application manual.