

Crumlin Bridge Protected with Spray Applied Waterproofing

ELIMINATOR® and Bond Coat 3 provide high performance adhesion combined with durability



Project Crumlin Bridge

Client Caerphilly County Borough Council

Contractor Dyer and Butler

Authorised Contractor Metrail

(Waterproofing Applicator)

GCP Solutions ELIMINATOR® Bridge Deck Waterproofing System, METASET® concrete system, Bond Coat 3

Project

Choosing a quick curing solution

The Crumlin Bridge was leaking, with corrosion evident in the structure. It required a new waterproofing solution as part of the refurbishment works to the bridge. In addition, due to the schedule of works, the project team required a solution that would enable the tack coat to be trafficked prior to laying the asphalt.

The bridge became another structure to benefit from the third generation bond coat in conjunction with the market leading ELIMINATOR waterproofing system from Stirling Lloyd (now GCP Applied Technology). The development of Bond Coat 3 represents a major leap forward in the provision of high-performance, heat activated bond coats.

Keeping Traffic Moving

Factors such as possession working, limited access, restricted working hours, and traffic management all needed to be considered. Since there wasn't going to be a full road closure on this site, the refurbishment works had to be split into two phases over a short period of time. This included deck preparation, installation of expansion joints, application of the waterproofing system and the installation of curbs, followed by the asphalt binder and surfacing courses.



A waterproofing solution to aid project completion

The specifier selected ELIMINATOR , which is based on unique ESSELAC technology, as well as Bond Coat 3, a cold reactive resin system providing a durable, protective finish, resistant to site damage with unlimited open time prior to application of the surfacing.

Prior to application, shot blasting and fine milling was carried out, with the METASET concrete system being used to repair rough and damaged areas of the bridge deck in preparation to receive the waterproofing system. The deck was primed to seal the deck and promote excellent bond between the deck and the membrane.

The ELIMINATOR membrane was then cold spray-applied and checked using a wet film gauge to confirm the required coverage and thickness had been achieved. Once the waterproofing membrane had been applied and left approximately 30 minutes to cure, it was electrically integrity tested (holiday detection test) to confirm that a defect-free, fully waterproof barrier had been achieved.

Bond Coat 3 was then spray-applied. The durability and unlimited open time of Bond Coat 3, allowed flexibility in the schedule and the following trades to proceed in compliance with the programme of works without unnecessary delays, saving time, money and further disruption. Due to the success of the project on the first 1150 metres of carriageway, the second phase of the project went ahead as planned completing the refurbishment of the Crumlin Bridge.

Blue 360 ^{sм} Total Business Advantage.

The power of GCP products, performance and people



gcpat.uk | United Kingdom customer service: +44 (0) 1480 478421

This document is only current as of the last updated date stated below and is valid only for use in the United Kingdom. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.uk. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.