

DARACEM[®] 153 (FM)

Superplasticizer for concrete acc. to EN 934-2:T3.1/3.2

Fields of Application

Daracem[®]153 (FM) has very strong water reducing and plasticizing properties without any retarding side effects. Thus, it is particularly suited to the production of concretes with high early strength, as well as mixes requiring high flow for the manufacture of difficult construction components.

Preliminary tests according to official national standards are always required before use!

Technical Data

Form	Liquid
Color	Brown
Density	1,23 ± 0,03 g/cm
pH-value	9,0 ± 1,0
Total chloride content	< 0,10 M.-%
Water-soluble chloride content	< 0,10 M.-%
Alkali content	< 8.5 m.-%
Storage	Keep secure in original containers. Protect from excessive heat and frost.
Recommended Dosage Range	0,20 – 3,32 M.-% of cement
Physiological effect	May irritate skin and eyes; see SDS
Shelf-life	approx. 1 year in closed original containers

Dosage and Use

Best results are obtained when added to the mix as the last component and when at least mixed for an additional 60 seconds.

gcpat.uk | United Kingdom customer service: +44 (0) 1480 478421

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

DARACEM is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2018 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Applied Technologies (UK) Ltd, 487-488 Ipswich Road, Slough, SL1 4EP

This document is only current as of the last updated date stated below and is valid only for use in the United Kingdom. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.uk. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2022-11-24

gcpat.uk/solutions/products/daracem-153-fm