

V-MAR[®] 10 P

Cohesion agent for pump and underwater concrete mixes

Product Description

V-MAR®10 P is a colloid based product giving the concrete a fattier, creamy consistency. V-MAR®10 P produces a more cohesive, highly workable concrete.

Advantages

- Greatly reduced underwater washout
- Improved pumping qualities
- Reduced pumping pressures, and improved pumping distances
- Reduced segregation

Typical Properties

Appearance	Very light beige powder
Apparent Density	0.65 - 0.75
Sensitivity to Humidity:	Lumps formed if kept outdoors
Chloride Content	< 0.1%
Non toxic, biodegradable and environmentally friendly	

Method Of Use

V-MAR®10 P is supplied in water soluble bags and can be added to the concrete at anytime during the batching cycle. Depending on the dosage level it may be necessary to mix for an additional 1 to 2 minutes, as a slight temporary stiffening may occur at the start of mixing process, this temporary condition is generally associated with high dosage levels.

The addition of V-MAR®10 P will have no noticeable effect on the following:

- air contents
- short, medium or long term mechanical properties

For underwater concrete, it is recommended that a superplasticiser is used with V-MAR®10 P in order to increase the workability to make the concrete suitable for placing by tremie or other suitable means.



Dosage Rate

Improved pumping and anti-segregation: 50 - 150 gms/m³. Underwater concrete: 0.1 - 0.5% of cement weight (normal average dose 0.3%). Compatible with all cement types.

Packaging

1.2 kg water soluble bags with 12 x 1.2 kg in a plastic tub.

150 g water soluble bags with 80 x 150 g in a plastic tub.

Storage & Transport

2 years in original, properly sealed packaging Do not store in damp conditions. Transport is Not regulated.

Health and Safety

For further information on Health and Safety matters regarding this product we recommend that you consult the relevant Safety Data Sheet from GCP Applied Technologies.

In line with general chemical handling precautions avoid contact with skin or eyes and protective gloves/goggles should be worn.

Technical Service

Our Technical Service department of GCP Applied Technologies is available to assist you in the correct use of our performance chemicals.

gcpat.uk | United Kingdom customer service: +44 (0) 1925 855330 Fax: 01925 855350

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

V-MAR is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2020 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies (UK) Ltd, Gate St, Dukinfield SK16 4RU.

This document is only current as of the last updated date stated below and is valid only for use in the United Kingdom. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.uk. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.