

# OPTEC<sup>®</sup> EC-111

Admixture for enhancing high-quality surfaces and for reducing efflorescence  
Waterproofing admixture for concrete in accordance to EN 934-2:T9

## Product Description

OPTEC<sup>®</sup>EC-111 is used for enhancing all high-quality concrete elements that require efflorescence reduced surfaces and intense colours. Most important examples for application include the production of slabs, interlocking pavement, kerbstones, palisades, masonry elements, etc.

## Properties/Mode of Action

- The active substances of OPTEC<sup>®</sup> EC-111 make the walls of capillary pores water-repellent and reduce the capillary suction effect.
- The transport of dissolved calcium hydroxide to the surface is impaired and thereby, the tendency to effloresce is significantly reduced.
- Surface-active substances create a better dispersion of the cement particles, making the concrete more homogenous and easier to compact.
- Superficial slurries that are generated during vibration effect close the textured surfaces.
- Moisture is reduced in the capillaries. A better dispersion of colour pigments allows a more intense and even dyeing of the concrete.

## Dosage and Use

OPTEC<sup>®</sup>EC-111 is added to the gauging water or onto the ready mix. The concrete should be run as moist as possible in order to increase the effect of OPTEC<sup>®</sup>EC-111

## Typical Properties

Effective component	Fatty acid
Form	Liquid
Homogeneity	Homogeneous (proved acc. to DIN V 20000-100, annex A)
Colour	White
Dry material content	Liquid
Density	1.00 ± 0.02 g/cm <sup>3</sup>
Freezing point	Approx. 0°C
pH-value	6.0 ± 1
Total chloride content	< 0.10 m.-%
Water-soluble chloride content	< 0.10 m.-%

Alkali content	Approx. 0.5 m.-%
Storage	Protect from frost
Recommended dosage	0.20–2.30 m.-% of cement
Delivery form	1000 kg containers; 220 kg drums; 23 kg cans
Physiological effect	May irritate skin and eyes; see MSDS.
Shelf-life	Approx. 6 month in closed original containers

gcpat.uk | United Kingdom customer service: +44 (0) 1925 855330 Fax: 01925 855350

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

OPTEC is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2020 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies (UK) Ltd, Gate St, Dukinfield SK16 4RU.

This document is only current as of the last updated date stated below and is valid only for use in the United Kingdom. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on [www.gcpat.uk](http://www.gcpat.uk). Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-05-13

[gcpat.uk/solutions/products/masonry-and-hardscape-solutions/optec-ec-111](http://gcpat.uk/solutions/products/masonry-and-hardscape-solutions/optec-ec-111)